

# Toshiba 2010E



Whether it is being used indoors or outdoors, the rich, vivid images delivered by the TR2010E LED Display System can bring any event to life. This versatile 10mm system offers high brightness and resolution, can be used in modular or fixed format and has quick build and easy maintenance characteristics. Add the fact it is IP65 classified, guaranteeing high levels of water protection, and the 2010E is ideal for all events, all year round.

\* If you have technical questions about this product, please contact Kristian Ulriksen +46 (0) 10 454 01 36. If you wish to make a reservation for this product, please call Lars Mossberg +46 303 20 85 00. Thank you for your interest!

## Technical data, Toshiba 2010E

### Screen

Type: Indoor/Outdoor

Tile size W x H x D: 640 x 480 x 234 mm

Max stacking/rigging: 15/15

Weight: 35 kg/tile

Weight/sqm: 114 kg

LEDs/pixel: 1R 1G 1B

Pixel pitch: 10 mm

Resolution: 64 x 48/tile

Pixel density: 10000 LEDs/sqm

Brightness: 5000 Nit

Colours: 10 bit/1 billion

Viewing Angle h/v: 120°/10° up/30° down

Power consumption: 260 W/tile

Contrast: 1:1200

Refresh rate: 800 hz

Ingress protection (front/back): IP65/IP54

Recommended min. viewing dist: 10 m